



品牌 BRAND		TONLY
车型 Model		TLD125
质量参数 Weight Parameters	总质量 Gross vehicle weight (T)	137
	额定装载质量 Rated payload (T)	91
	整车整备质量 Curb weight (T)	46
整车主要技术参数 Whole Vehicle Main Technical parameters	外廓尺寸（长×宽×高）mm Overall dimensions (LxWxH) mm	11100 x 4443 x 4452
	轴距 Wheel base (mm)	4050+1900
	驱动型式 Driving type	6×4
	最高行驶速度 Max.speed (km/h)	40
	最小转弯直径 Min.turning diameter (m)	22
	最大爬坡度 Max. gradeability (%)	30
	最小离地间隙 Min. ground clearance (mm)	438
	制动距离（车速为 30km/h）m Braking Length (30km/h) m	23

	接近角/离去角 Apporach/Departure Angle (°)	21/49
	型号 Type	YUCHAI YCK16 775 (Euro III Emission)

发动机 Engine	型式 Model	直列、六缸、四冲程水冷直喷涡轮增压柴油发动机 Inline, six-cylinder, four-stroke water-cooled direct injection turbo-charged diesel engine
	排量(L) Displacement(L)	16
	马力/HP	570kW/775 hp
整车主要性能参数 Whole Vehicle Main Configurations	变速箱 Transmission	法士特 FAST 8DS280 带液力缓速功能 With hydraulic retarder function
	制动系统 BraKing System	双回路气制动 Dual circuit air brake
	前桥 Front axle	40 吨前桥/独立式转向桥 40T HANDE independent steering axle
	后桥总成 Middle & rear axle	60 吨+60 吨中后桥/驱动桥，盘式制动器 60T+60T HANDE driving axle, disc brake
	悬挂系统	全车油气悬架 Full hydro pneumatic suspension
	车架 Frame	焊接式车架,关键部位采购铸件结构 Welding frame, key parts procurement casting structure
	驾驶室 Cabin	单边全刚性防落物驾驶室(左驾) Single whole rigid narrow left cabin
	转向系统 Steering System	全液压转向系统 Full hydraulic steering system
	举升系统 Lifting System	海沃 HYVA FEA214
	货箱规格和材质 Specification of the cargo body	V 型货箱，堆装 53m³/平装 45m³；底板厚度 18mm、前板、侧板厚度 12mm，材质耐磨板 NM400。货箱内径：6280*4000*2370 mm。 V type bucket capacity: Heaped 53m³/Struck 45m³. Bottom plate thickness 18mm, front and side plate thickness 12mm, wear resistant steel plate. Inner size: 6280*4000*2370 mm.
	油箱容积 Fuel Tank (L)	700
	轮胎规格 Tire size	18.00R25 E4
车身油漆颜色 Body paint color		工程黄 Engineering Yellow
*The final explanation right belongs to TONLY		